



## HWSRL Hot Water Temperature maintenance Heater Tape

Applications: Hot Water Temperature Maintenance up to 65°C

A self-Regulating heater cable designed for Hot Water Temperature Maintenance of metal pipework - to give you hot water straight from the tap

### Power Outputs & Dimensions

	W/m at 55°C	Dimensions
HWSRL	12	12.7mm x 6.4mm

### Standard Specification

Classification	Safe Area
Traced Surface	Metal Pipes (for applications on plastic pipes, please consult MJA for further information regarding suitability and installation)
Chemical Resistance	Mild Inorganic Solutions
Maximum Exposure Temperature	85°C (intermittent)
Minimum Installation Temperature	- 50°C
Minimum Bend Radius	35mm
Maximum Circuit Lengths	100m
Voltage	230V

### Other

Approvals	CE Marked
-----------	-----------

*MJA recommends the use of a 30mA residual current device for maximum safety*

**MJA Heat Trace Products Ltd - 9 Gaskyns Close, Rudgwick, West Sussex RH12 3HE**

E: jane@mjaheattrace.co.uk | T: 01403 823560 | W: www.mjaheattrace.co.uk

Registered in England No:07146844

**Disclaimer:** Any information given is believed to be reliable. However, users should treat this information as a guideline, and independently evaluate the suitability of the product for their particular application. MJA Heat Trace Products Limited makes no warranties as to the accuracy and completeness of the information and disclaims any liability regarding its use.