



### SRM Self-Regulating Heater Tape

Applications: Temperature maintenance up to 95 °C.

#### Power Outputs & Dimensions

	W/m at 10°C	Geometry	Dimensions
SRM30	30	Large	13.4mm x 6.7mm
SRM50	45	Large	13.4mm x 6.7mm

#### Standard Specification

Classification	Safe Area and ATEX Approved (T5) for Hazardous Areas	
Traced Surface	Metal Pipes (for applications on plastic pipes, please consult MJA for further information regarding suitability and installation)	
Chemical Resistance	Mild Inorganic Solutions	
Maximum Exposure Temperature	100°C (intermittent)	
Minimum Installation Temperature	- 50°C	
Minimum Bend Radius	35mm	
	<b>Max Circuit Length</b>	
	<b>110V</b>	<b>230V</b>
<b>SRM30</b>	60m	120m
<b>SRM50</b>	-	80m

#### Options

Fluoropolymer Outer Jacket	This option is recommended for applications where increased chemical resistance is required.
Voltage	110V (Only available as an option for SRM30) 230V

## Other

Other Hazardous Area Classifications	IECEX and GOST Approved
--------------------------------------	-------------------------

*MJA recommends the use of a 30mA residual current device for maximum safety*

**MJA Heat Trace Products Ltd - 9 Gaskyns Close, Rudgwick, West Sussex RH12 3HE**

**E:** jane@mjaheattrace.co.uk | **T:** 01403 823560 | **W:** www.mjaheattrace.co.uk

Registered in England No: 07146844

**Disclaimer:** Any information given is believed to be reliable. However, users should treat this information as a guideline, and independently evaluate the suitability of the product for their particular application. MJA Heat Trace Products Limited makes no warranties as to the accuracy and completeness of the information and disclaims any liability regarding its use.